

Area real disponible o eficiencia para sistemas de tamices

diám. alambre (pulgadas)	apertura (pulgadas)	diám. alambre mm	apertura mm	porcentaje/eficiencia (%)
0.045	0.01	1.14	0.25	18.2
0.045	0.02	1.14	0.51	30.8
0.045	0.03	1.14	0.76	40.0
0.045	0.04	1.14	1.02	47.1
0.045	0.06	1.14	1.52	57.1
0.063	0.01	1.60	0.25	13.7
0.063	0.02	1.60	0.51	24.1
0.063	0.03	1.60	0.76	32.3
0.063	0.04	1.60	1.02	38.8
0.063	0.06	1.60	1.52	48.8
0.069	0.01	1.75	0.25	12.7
0.069	0.02	1.75	0.51	22.5
0.069	0.03	1.75	0.76	30.3
0.069	0.04	1.75	1.02	36.7
0.069	0.06	1.75	1.52	46.5
0.093	0.01	2.36	0.25	9.7
0.093	0.02	2.36	0.51	17.7
0.093	0.03	2.36	0.76	24.4
0.093	0.04	2.36	1.02	30.1
0.093	0.06	2.36	1.52	39.2
0.12	0.01	3.05	0.25	7.7
0.12	0.02	3.05	0.51	14.3
0.12	0.03	3.05	0.76	20.0
0.12	0.04	3.05	1.02	25.0
0.12	0.06	3.05	1.52	33.3

Area real disponible o eficiencia para sistemas de rejillas/barras (planchuelas)

espesor de barra (pulgadas)	apertura entre rejillas (pulgadas)	espesor de barra mm	apertura entre rejillas mm	porcentaje/eficiencia
0.25	0.50	6.4	12.7	66.7
0.25	0.75	6.4	19.1	75.0
0.25	1.00	6.4	25.4	80.0
0.25	1.25	6.4	31.8	83.3
0.25	1.50	6.4	38.1	85.7
0.31	0.50	7.9	12.7	61.5
0.31	0.75	7.9	19.1	70.6
0.31	1.00	7.9	25.4	76.2
0.31	1.25	7.9	31.8	80.0
0.31	1.50	7.9	38.1	82.8
0.38	0.50	9.5	12.7	57.1
0.38	0.75	9.5	19.1	66.7
0.38	1.00	9.5	25.4	72.7
0.38	1.25	9.5	31.8	76.9
0.38	1.50	9.5	38.1	80.0
0.44	0.50	11.1	12.7	53.3
0.44	0.75	11.1	19.1	63.2
0.44	1.00	11.1	25.4	69.6
0.44	1.25	11.1	31.8	74.1
0.44	1.50	11.1	38.1	77.4
0.50	0.50	12.7	12.7	50.0
0.50	0.75	12.7	19.1	60.0
0.50	1.00	12.7	25.4	66.7
0.50	1.25	12.7	31.8	71.4
0.50	1.50	12.7	38.1	75.0